#### **SECTION 06100: ROUGH CARPENTRY**

# PART 1 – GENERAL

#### 1.01 SUMMARY

- A. Provide rough carpentry:
  - 1. Framing with pressure-treated dimension lumber for handrail system.
  - 2. Miscellaneous Lumber

# 1.02 QUALITY ASSURANCE

- A. Comply with governing codes and regulations. Provide products of acceptable manufacturers, which have been in satisfactory use in similar service for three years. Use experienced installers. Deliver, handle, and store materials as required to preserve appearance and quality.
- B. Lumber Standards and Grade Stamps: DOC PS 20 and agency grade stamps.
- C. Preservative Treatment: AWPA C2 waterborne pressure treatment.

### PART 2 – PRODUCTS

#### 2.01 MATERIALS

- A. Dimension Lumber:
  - 1. Handrail Posts and Blocking: Hem-Fir Select Structural
  - 2. Framing between posts: Douglas Fir Select Structural
  - 3. Cap rail: Western Cedars, Select, Appearance Grade
  - 4. Miscellaneous Framing: Hem-Fir #1

DIVISION 6 — CARPENTRY Section 06100: Rough Carpentry PART 3 — EXECUTION

# 3.01 INSTALLATION

- A. Securely attach rough carpentry work to substrate by anchoring and fastening as indicated,
- B. Provide nailers and blocking where required. Set work plumb, level and accurately cut.
- C. Repair all cuts and holes per AWPA C-2 before installation.
- D. Restore damaged components. Protect work from damage.

# **END OF SECTION 06100**

Technical Specifications Rev. 02/20/04